

Patent
62478-6017

IN THE CLAIMS:

1. (Previously Presented) A plasma display panel (hereinafter referred to as "PDP") driving method for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a set-up step for applying a set-up pulse to each of the plurality of discharge cells to accumulate a charge in each discharge cell;

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and

a discharge sustain step for applying at least one sustain pulse to each discharge cell after the write step to perform a sustain discharge in the selected discharge cells,

wherein the set-up pulse applied during the set-up step has a staircase waveform that rises in at least two steps and a voltage jump for a first-step rise of the staircase waveform being no less than $V_f - 70V$ but no greater than V_p when V_f is a discharge starting voltage.

2. (Original) The PDP driving method of Claim 1, wherein:
the staircase waveform for the set-up pulse is a staircase waveform that falls in at least two steps.

3. (Previously Presented) The PDP driving method of Claim 1, wherein an average rate of change of voltage from the end of a first-step rise to the end of a second step rise in the waveform for the set-up pulse is no less than $1V/\mu s$ but no greater than $9V/\mu s$.

BEST AVAILABLE COPY

Patent
62478-6017

4. (Previously Presented) The PDP driving method of Claim 1, wherein a voltage jump for the first-step rise in the waveform for the set-up pulse is no less than $V_f - 70V$ but no greater than V_f when V_f is a discharge starting voltage.

5. (Previously Presented) A PDP driving method for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a set-up step for applying a set-up pulse to each of the plurality of discharge cells to accumulate a charge in each discharge cell;

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and

a discharge sustain step for applying at least one sustain pulse to each discharge cell after the write step to perform a sustain discharge in the selected discharge cells,

wherein the set-up pulse applied during the set-up step has a staircase waveform that falls in at least two steps and a ratio of a first-step voltage Fall (V_f) to a peak voltage (V_m) being no less than 0.05:1, and no more than 0.8:1, and a ratio of (a) a time (t_p) from an end of the first-step fall to a start of a second-step fall to (b) pulse width (t_w) being no less than 0.05:1 and no more than 0.6:1.

6. (Previously Presented) The PDP driving method of Claim 1, wherein the staircase waveform for the set-up pulse is generated by adding at least two pulses and applying the resulting pulse.

BEST AVAILABLE COPY

Patent
62478-6017

7. (Previously Presented) A PDP driving method, for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and

a discharge sustain step for applying at least one sustain pulse to each discharge cell after the write step to perform a sustain discharge in the selected discharge cells;

wherein the write pulse applied in the write step has a staircase waveform that falls in at least two steps and a peak voltage of no less than 70V but no more than 100V, and a pulse width of no less than 0.5 μ s but no more than 2.00 μ s.

8. (Original) The PDP driving method of Claim 7, wherein the staircase waveform of the write pulse applied in the write step rises in at least two steps.

9. (Previously Presented) The PDP driving method of Claim 7, wherein a voltage jump for a second-step rise in the waveform for the write pulse is no less than 10V but no greater than 100V.

10. (Previously Presented) A PDP driving method, for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and

a discharge sustain step for applying at least one sustain pulse to each discharge cell after the write step to perform a sustain discharge in the selected discharge cells;

62478.6017PRICE/IRV461101

BEST AVAILABLE COPY

Patent
62478-6017

wherein the write pulse applied in the write step has a staircase waveform that rises in at least two steps and a peak voltage of no less than 70V but no more than 100V, and a pulse width of no less than 0.5 μ s but no more than 2.0 μ s.

11. (Previously Presented) The PDP driving method of Claim 7 and Claim 10, wherein the staircase waveform of the write pulse in the write step is generated by adding at least two pulses and applying the resulting pulse.

12-15. (Cancelled)

16. (Previously Presented) A PDP driving method, for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and

a discharge sustain step for applying at least one sustain pulse to each discharge cell after the write step to perform a sustain discharge in the selected discharge cells;

wherein the sustain pulses applied in the sustain step have a staircase waveform that falls in at least two steps and a maximum voltage V that is no less than V_f but no greater than $V_f + 150V$, when V_f is a discharge starting voltage.

17. (Previously Presented) The PDP driving method of Claim 16, wherein the maximum voltage for the sustain pulses is no less than V_f , but no greater than $V_f + 150V$, when V_f is a discharge starting voltage.

18-23. (Cancelled)

62478.6017PRICE/URV481101

Patent
62478-6017

24. (Original) A PDP driving method, for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and

a discharge sustain step for applying at least one sustain pulse to each of the plurality of discharge cells after the write step to perform a sustain discharge in the discharge cells corresponding to the written image;

wherein the waveform for the sustain pulses applied in the sustain step is set such that a voltage applied when a discharge current is highest is higher than a voltage at the discharge starting point.

25. (Original) The PDP driving method of Claim 24, wherein:

the rise portion of the waveform for the sustain pulses is in the form of a linear or approximately linear slope that has a constant gradient.

26. (Previously Presented) The PDP driving method of Claim 16, wherein the waveform for each sustain pulse is such that a phase for a variation in the discharge current is set earlier than a phase for variation in a voltage applied to the discharge cells during a period in the pulse between a point where a discharge current starts and a point where the discharge current reaches a peak value.

27. (Previously Presented) The PDP driving method of Claim 16, wherein the waveform for the sustain pulses in the sustain step is generated by adding at least two pulses and applying the resulting pulse.

62478.6017/PRI/CS/VRV/481101

Patent
62478-6017

28. (Previously Presented) A PDP driving method, for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and

a discharge sustain step for applying at least one sustain pulse to each discharge cell after the write step to perform a sustain discharge in the selected discharge cells;

wherein only a first sustain pulse applied in the sustain step has a staircase waveform in which at least one of the rising and falling portions is performed in at least two steps.

29. (Original) The PDP driving method of Claim 28, wherein the first sustain pulse applies a maximum voltage for at least $0.1\mu\text{s}$ longer than for each of second and subsequent sustain pulses.

30. (Previously Presented) The PDP driving method of Claim 28, wherein the first sustain pulse applies the maximum voltage for at least $0.02\mu\text{s}$ but for no longer than 90% of a pulse width PW.

31. (Previously Presented) The PDP driving method of Claim 16, wherein the sustain step, the waveform for the sustain pulses is generated by adding at least two pulses and applying the resulting pulse.

62478.5017PRICEINRYV481101

Patent
62478-6017

32. (Previously Presented) A PDP driving method, for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image;

a discharge sustain step for applying at least one sustain pulse to each discharge cell after the write step to perform a sustain discharge in the selected discharge cells; and

an erase step for applying an erase pulse to each discharge cell after the discharge sustain step to erase the image,

wherein the erase pulse applied in the erase step has a staircase waveform that rises in at least two steps and a voltage in a first-step rise being no less than $V_f - 50V$ but no greater than $V_f + 30V$, when V_f is a discharge starting voltage.

33. (Cancelled)

34. (Previously Presented) The PDP driving method of Claim 32, wherein a voltage in a first-step rise in the waveform for the erase pulse is no less than V_f but no greater than $V_f + 100V$, when V_f is a discharge starting voltage.

35. (Original) A PDP driving method, for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image;

62478.6017PRICE/IRV461101

Patent
62478-6017

a discharge sustain step for applying at least one sustain pulse to each discharge cell after the write step to perform a sustain discharge in the selected discharge cells; and

an erase step for applying an erase pulse to each discharge cell after the discharge sustain step to erase the image,

wherein the waveform for the erase pulse applied in the erase step is a staircase waveform that rises in at least two steps; and

a time between a rise of the erase pulse and a point at which a maximum voltage ceases to be applied is no less than $T_{dr} - 0.1\mu s$ but no greater than $T_{dr} + 0.1\mu s$, when T_{dr} is a discharge delay time for the pulse.

36. (Original) The PDP driving method of Claim 35, wherein a first-step rise of the waveform for the erase pulse no less than V_f but no greater than $V_f + 100V$, when V_f is a discharge starting voltage.

37. (Previously Presented) The PDP driving method of Claim 32, wherein the waveform for the erase pulse in the erase 104 step is generated by adding at least two pulses and applying the resulting pulse.

38. (Original) A PDP driving method for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a set-up step for applying a set-up pulse to each of the plurality of discharge cells to accumulate a charge in each discharge cell;

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image;

62478.6017/PRICE/NRV481101

Patent
62478-6017

a discharge sustain step for applying at least one sustain pulse to each discharge cell after the write step to perform a sustain discharge in the selected discharge cells, and

an erase step for applying an erase pulse to each discharge cell after the discharge sustain step to erase the image,

wherein the waveforms for the set-up pulse applied in the set-up step, the write pulse applied in the write step, the first sustain pulse applied in the sustain step and the erase pulse applied in the erase step is a staircase waveform in which at least one of the rising and falling portions is performed in at least two steps.

39. (Original) A PDP driving method for a PDP in which a plurality of discharge cells are arranged between a pair of substrates, the PDP driving method repeating the following steps to perform image display:

a set-up step for applying a set-up pulse to each of the plurality of discharge cells to accumulate a charge in each discharge cell;

a write step for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image;

a discharge sustain step for applying at least one sustain pulse to each discharge cell after the write step to perform a sustain discharge in the selected discharge cells, and

an erase step for applying an erase pulse to each discharge cell after the discharge sustain step to erase an image,

wherein the waveforms for the set-up pulse applied in the set-up step, the write pulse applied in the write step, the sustain pulses applied in the sustain step and the erase pulse

Patent
62478-6017

applied in the erase step is a staircase waveform in which at least one of the rising and falling portions is performed in at least two steps.

40. (Previously Presented) The PDP driving method of Claim 32, wherein a discharge gas is enclosed in each of the discharge cells in the PDP at a pressure of 800 to 4 000 torr.

41. (Original) The PDP driving method of Claim 40, wherein an inert gas mixture including helium, neon, xenon and argon is used as the discharge gas.

42. (Previously Presented) The PDP driving method of Claim 40, wherein the discharge gas is a mixture containing not more than 55% xenon, not more than 0.5% argon and less than 55% helium.

43. (Original) A PDP display apparatus, comprising:

- a PDP in which a plurality of discharge cells are arranged between a pair of substrates; and
- a driving apparatus including:
 - a set-up unit for applying a set-up pulse to each of the plurality of discharge cells to accumulate a charge in each discharge cell;
 - a write unit for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and
 - a discharge sustain unit for applying at least one sustain pulse to each of the plurality of discharge cells to perform a sustain discharge in the discharge cells corresponding to the written image,

62478.6017*PRICENRYV481101

Patent
62478-6017

wherein the set-up unit includes a pulse adding means for generating the set-up pulse by adding at least two pulses.

44. (Original) A PDP display apparatus, comprising:

a PDP in which a plurality of discharge cells are arranged between a pair of substrates; and

a driving apparatus including:

a write unit for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and

a discharge sustain unit for applying at least one sustain pulse to each of the plurality of discharge cells to perform a sustain discharge in the discharge cells corresponding to the written image,

wherein the write unit includes a pulse adding means for generating the write pulse by adding at least two pulses.

45. (Previously Presented) A PDP display apparatus, comprising:

a PDP in which a plurality of discharge cells are arranged between a pair of substrates; and

a driving apparatus including:

a write unit for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and

a discharge sustain unit for applying at least one sustain pulse to each of the plurality of discharge cells to perform a sustain discharge in the discharge cells corresponding to the written image,

62478.6017P/CE/REV481101

Patent
62478-6017

wherein the discharge sustain unit includes an adding means for generating the each sustain pulse by adding at least two pulses.

46. (Original) A PDP display apparatus, comprising:

a PDP in which a plurality of discharge cells are arranged between a pair of substrates; and

a driving apparatus including:

a write unit for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image;

a discharge sustain unit for applying at least one sustain pulse to each of the plurality of discharge cells to perform a sustain discharge in the discharge cells corresponding to the written image; and

an erase unit for applying an erase pulse to each of the plurality of discharge cells to erase an image,

wherein the erase unit includes a pulse adding means for generating the erase pulse by adding at least two pulses.

47. (Original) A PDP display apparatus, comprising:

a PDP in which a plurality of discharge cells are arranged between a pair of substrates; and

a driving apparatus including:

a write unit for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image; and

BEST AVAILABLE COPY

Patent
62478-6017

a discharge sustain unit for applying at least one sustain pulse to each of the plurality of discharge cells to perform a sustain discharge in the discharge cells corresponding to the written image,

wherein the waveform for the write pulse applied by the write unit and the sustain pulses applied by the discharge sustain unit have staircase waveforms in which at least one of the rising and falling portions has at least two steps.

48. (Original) A PDP display apparatus, comprising:

a PDP in which a plurality of discharge cells are arranged between a pair of substrates; and

a driving apparatus including:

a set-up unit for applying a set-up pulse to each of the plurality of discharge cells to accumulate a charge in each discharge cell;

a write unit for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image;

a discharge sustain unit for applying at least one sustain pulse to each of the plurality of discharge cells to perform a sustain discharge in the discharge cells corresponding to the written image; and

an erase unit for applying an erase pulse to each of the plurality of discharge cells to erase an image,

wherein the set-up pulse applied by the set-up unit, the write pulse applied by the write unit, the first sustain pulse applied by the discharge sustain unit and the erase pulse applied

Patent
62478-6017

by the erase unit have staircase waveforms in which at least one of the rising and falling portions is performed in at least two steps.

49. (Original) A PDP display apparatus, comprising:

a PDP in which a plurality of discharge cells are arranged between a pair of substrates; and

a driving apparatus including:

a set-up unit for applying a set-up pulse to each of the plurality of discharge cells to accumulate a charge in each discharge cell;

a write unit for applying a write pulse to selected discharge cells of the plurality of discharge cells to write an image;

a discharge sustain unit for applying at least one sustain pulse to each of the plurality of discharge cells to perform a sustain discharge in the discharge cells corresponding to the written image; and

an erase unit for applying an erase pulse to each of the plurality of discharge cells to erase an image,

wherein the set-up pulse applied by the set-up unit, the write pulse applied by the write unit, and the sustain pulses applied by the discharge sustain unit and the erase pulse applied by the erase unit have staircase waveforms in which at least one of the rising and falling portions is performed in at least two steps.

50. (Previously Presented) The PDP display apparatus of Claim 48, wherein the discharge gas is enclosed in each of the discharge cells in the PDP at a pressure of 800 to 4 000 torr.